

Wet Hopper Destoner



FLEXIBLE

- Seven models available with storage capacities of up to 15 t (33,000 lb)
- Out-feed capacities of up to 60 t/hr (132,000 lb)
- Adjustable out-feed elevator length and base frame height to suit your line
- Variable speed control of out-feed elevator
- Stand-alone electrical enclosure*
- Water inlet valve & float switch controls to manage water filling*

ROBUST

- Durable, robust design with stainless steel construction
- Double bar cleats on elevator for increased cleat durability*

EFFECTIVE

- Choice of stone lock valve or upgrade to stone elevator to remove stones & clods
- Rubber web bars for gentle vegetable handling
- Internal spray jets to assist with the flow of vegetables along the tank
- Air agitation for improved dirt removal while maintaining gentle vegetable handling*
- Water spray bars to remove any remaining soil and floating debris from vegetables before exiting the hopper*


SMART

- Easy access for cleaning and maintenance via inspection hatches
- Internal cleaning bars to clean out hard to reach parts of the hopper
- Water overflow to keep the water level constant by expelling excess water
- Conveyor / out-feed elevator lifts out of the hopper to allow for easy cleaning, servicing and maintenance

HELPFUL

- Self-cleaning with soil collection hopper and manual or automatic* water and dirt discharge valves. The system is capable of removing several tonnes of dirt per day
- Comprehensive worldwide spare parts, service and installation support network

*Options




Equipment Description

The Wyma Wet Hopper Destoner significantly improves your washing performance further down the processing line whilst providing the additional benefit of removing stones and clods. It acts as a pre-soak and dirt/rubbish collection facility ensuring that this material is not transferred to other equipment in your processing line.

The standard stone lock system discharges stones and clods via a holding chamber at the base of the Wet Hopper Destoner. The system is pneumatically actuated and stone and clods are removed on a discrete basis at regular intervals. The frequency of the stone and clod removal can be varied according to your operating conditions.

The optional stone elevator system (upgrade from stone lock) discharges stones and clods on the side of the Wet Hopper Destoner where bins (or other loading item) can be placed. Stones and clods are removed on a continuous basis which makes the stone elevator a recommended feature for customers who have large quantities of stones and clods coming from the field.





Wyma Wet Hopper Destoner - Stone Lock



Wyma Wet Hopper Destoner - Stone Elevator

- A** Curved shape water holding tank with buffer storage capacity
- B** Adjustable base frame height
- C** Inspection hatches for easy access
- D** Stone lock discharge system
- E** Internal spray jets to push produce forward
- F** Optional water spray bars to remove remaining soil and floating debris
- G** Various elevator height and speed available to set an even flow for your line
- H** Rubber web bars for gentle produce handling
- I** Air agitation system to aid pre-cleaning of vegetables
- J** Stone elevator discharge system

Technical Data:

Wet Hopper Destoner - Stone Lock					
Model	Size	Mass (empty)	Max Out-Feed Capacity*	Tank Length	Overall Length
HWS0400	4 t	3.5 t (7,716 lb)	30 t (66,139 lb)	4,745 mm (15'6")	5,840 mm (19'2")
HWS0600	6 t	3.8 t (8,378 lb)	30 t (66,139 lb)	6,245 mm (20'5")	7,340 mm (24'1")
HWS0800	8 t	4.7 t (10,362 lb)	45 t (99,208 lb)	7,745 mm (25'4")	8,840 mm (29'0")
HWS1000	10 t	5.5 t (12,125 lb)	45 t (99,208 lb)	9,245 mm (30'3")	10,340 mm (33'9")
HWS10001**	10t	5.7 t (12,566 lb)	60 t (132,277 lb)	7,831 mm (25'7")	9,700 mm (31'8")
HWS1200	12 t	6.1 t (13,448 lb)	45 t (99,208 lb)	10,745 mm (35'3")	11,840 mm (38'8")
HWS1500**	15 t	6.9 t (15,212 lb)	60 t (132,277 lb)	10,831 mm (35'5")	12,700 mm (41'7")

Wet Hopper Destoner - Stone Elevator				
Model	Size	Mass (empty)	Tank Length	Overall Length
HWD0400/HWE0400	4 t	3.9 t (8,598 lb)	4,745 mm (15'6")	6,325mm (14'2")
HWD0600/HWE0600	6 t	4.7 t (10,362 lb)	6,245 mm (20'5")	7,825mm (25'7")
HWD0800/HWE0800	8 t	5.4 t (11,905 lb)	7,745 mm (25'4")	9,325mm (30'6")
HWD1000/HWE1000	10 t	6.1 t (13,488 lb)	9,245 mm (30'3")	10,825 mm (35'5")
HWD10001**/HWE10001**	10 t	6.5 t (14,330 lb)	7,831 mm (25'7")	9,700 mm (31'8")
HWD1200/HWE1200	12 t	6.8 t (14,991 lb)	10,745 mm (35'3")	12,325 mm (40'4")
HWD1500**/HWE1500**	15 t	7.7 t (16,976 lb)	10,831 mm (35'5")	12,700 mm (41'7")

* Max out-feed capacity is the same for both the Stone Lock and Stone Elevator

** Extra wide out-feed elevator

Wyma Fresh Thinking

When you've worked hard to cultivate a successful growing and packing business and you're aiming to deliver a quality product, you want the best post-harvest handling solutions available.

When you buy Wyma, you buy proven technical innovation and quality, backed up by a deep understanding of your processing needs. We hope you will be as proud to be a Wyma owner as we are to manufacture and support the equipment worldwide.

Our fresh thinking is always available to help you keep improving the way you process your vegetables. As we say, "if it's worth growing, it's worth handling with Wyma".

Insist on authentic Wyma spare parts



Consult



Design



Manufacture



Install



Support

Contact Details

New Zealand Head Office

27 Foremans Road
PO Box 16-707
Hornby 8441
Christchurch
New Zealand
P: +64 3 344 6403
F: +64 3 344 6407
sales@wymasolutions.com


European Office

Wyma Europe s.r.o.
Netovicka 875
27444
Slany
Czech Republic
P: +420 312 312 733
F: +420 312 312 734
eu.sales@wymasolutions.com

Australian Contact

580 Doyles Road
PO Box 1158
Shepparton
Victoria 3630
Australia
P: +61 400 577 921
F: +61 3 5831 1038
au.sales@wymasolutions.com

Your Local Wyma Representative:



The information contained in this document is based upon the latest information available at the time of publication. We make no guarantees or representations as to its accuracy. We are continually updating and improving our products and reserve the right to amend, discontinue or alter specifications and prices without prior notice. © Wyma